

チャンピオンバッテリー

形式	容量(Ah)			CCA at- 18COF.	CCA at- 0C32F.	Short Circuit Amps	Internal Resistance Ohms	寸法 (mm)						端子形状	重量 (kgs)	
	C/100 1.80vpc	C/20 1.75vpc	C/5 1.75vpc					L		W		H				
								inch	mm	inch	mm	inch	mm		kg	lbs
6TLG130*	130	120	92.9	760	1010	3200	3	7.68	195	6.69	170	8.13	207	FT4	16	35.2
6TLG220*	211	200	155	1150	1440	5000	2.3	12.7	323	7.01	178	9.25	235	FT5	31.5	69.3
6TLG250	255	230	178	1240	1650	5400	2.1	9.57	243	7.4	188	10.8	275	FT5	35.5	77
12TLG20	18.8	17	13.2	110	165	750	12	7.07	180	2.99	76	6.61	168	FT3	6	13.2
12TLG30	28.8	26	20.1	190	250	1100	8.2	6.54	165	4.96	127	6.93	176	FT3	10	22
12TLG40	34.3	31	24	240	320	1500	7.3	7.72	196	5.16	131	6.34	161	FT3	12	26.4
12TLG50	46.5	42	32.5	260	350	1700	6	7.76	197	6.54	166	6.69	170	FT3	14	30.8
12TLG60	60.9	55	42.6	280	380	1900	5.6	9.02	229	5.43	138	8.43	214	FT3	18.7	41.1
12TLG70	72	65	50.6	390	510	2000	5.5	13.8	350	6.61	168	7.05	179	FT3	21.3	46.9
12TLG80	77.5	70	54.2	410	550	2100	5.4	10.2	259	6.61	168	8.44	215	FT3	25	55
12TLG90	88.6	80	61.9	460	620	2400	4.5	10.2	259	6.61	168	8.46	215	FT3	28	61.6
12TLG100	99.6	90	69.7	510	680	2650	4.3	12.1	307	6.65	169	8.46	215	FT3	29.5	64.9
12TLG110	111	100	77.4	580	780	2900	3.9	13	330	6.69	170	8.46	215	FT4	30	66
12TLG120	122	110	85.1	710	960	3000	3.4	13	330	6.69	170	8.46	215	FT4	33	72.6
12TLG130	133	120	92.9	760	1020	3300	3.1	16.1	409	6.97	177	8.86	225	FT4	39	85.8
12TLG150	151	136	105	970	1300	4200	2.9	13.5	342	6.81	173	11.2	285	FT4	42	92.4
12TLG170	168	152	118	1060	13900	4500	2.7	19	483	6.69	170	9.49	241	FT5	47.5	105
12TLG190	190	171	132	1100	1410	4600	2.5	20.9	530	8.23	209	8.86	225	FT5	53.4	117
12TLG210	211	1190	147	1150	1440	4700	2.3	20.9	530	8.23	209	8.86	225	FT5	56.3	124
12TLG250	255	230	178	1240	1670	5400	2.2	20.6	522	9.45	240	8.86	225	FT5	61.5	135
12TLG300	294	265	205	1240	1670	5400	2.2	20.6	522	9.45	240	8.46	215	FT5	76	167