

フルリバーバッテリー

Model	Industry Ref.	Capacity(minutes)		Capacity(AH)		Cranking(Amps)		Terminal Type	Dimensions-Inches(mm)			Weight lbs (kg)
		@ 25 Amps	@ 75 Amps	@ 5 Hr Rate	@ 20 Hr	CA @32°	CCA @0°F		Length	Width	Height	
2 Volt Deep Cycle - Sealed-Maintenance Free AGM Batteries												
DC1150-2	903/L16	2235	658	945	1150	-	-	M10 or DT	11.61(295)	7.05(179)	16.18(411)	126.99(57.6)
6Volt Deep Cycle - Sealed-Maintenance Free AGM Batteries												
DC200-6	27	400	100	1654	200	-	-	M6 / M8	12.05(306)	6.65(169)	8.90(226)	66.1(30.0)
DC220-6	27	425	112	180	220	1350	1120	M8	12.05(306)	6.85(174)	8.90(226)	72.1(32.7)
DC224-8	GC2	441	113	179	224	1080	900	M8-TP08	10.24(260)	7.09(180)	9.88(251)	65.7(29.8)
DC245-6	DIN	457	120	198	245	1120	930	AP	9.61(244)	7.48(190)	10.83(275)	71.2(32.3)
DC250-6	GC2	531	135	204	250	1160	960	M8-TP08	10.31(262)	7.13(181)	10.71(272)	76.1(34.5)
DC335-6	902/J305	751	184	274	335	1560	1300	DT	11.61(295)	7.00(178)	14.41(366)	105.4(47.8)
DC400-6	903/L16	885	229	340	415	1800	1500	DT	11.61(295)	7.00(178)	16.69(424)	123.5(56)
8Volt Deep Cycle - Sealed-Maintenance Free AGM Batteries												
DC160-8	GC8	315	112@ 56 Amps	131	160	-	-	M8	10.24(260)	7.17(182)	10.71(272)	69.9(31.7)
DC180-8	GC8	335	125@ 56 Amps	147.5	180	-	-	M8	10.24(260)	7.17(182)	10.71(272)	80.5(36.5)
DC160-10	GC8H	390	140@ 56 Amps	164	200	-	-	M8	10.24(260)	7.17(182)	11.77(299)	88.2(40)
12Volt Deep Cycle - Sealed-Maintenance Free AGM Batteries												
DC35-12	U1	52	-	29	35	275	225	M6	7.72(196)	5.16(131)	7.09(180)	25.4(11.5)
DC40-12	U1L	50	-	32.8	40	320	275	M6	7.80(196)	6.54(166)	6.85(174)	29.5(13.4)
DC55-12	22NF	96	-	45	55	480	400	M6	9.02(229)	5.43(138)	8.35(212)	38.8(17.6)
DC60-12	48	100	30	49.2	60	485	410	AP	10.43(265)	6.54(166)	7.40(188)	45.6(20.7)
DC65-12	93	100	30	53.5	65	510	430	M6	13.82(351)	6.57(167)	6.93(176)	52.0(23.6)
DC70-12	24	115	31	57.5	70	540	450	M8-TP08	10.24(260)	6.65(169)	8.46(215)	52.5(23.8)
DC85-12	24	145	34	70	85	600	510	M8-TP08	10.24(260)	6.65(169)	8.46(215)	55.3(25.1)
DC105-12	27	175	43	86	105	820	680	M8-TP08	12.09(307)	6.65(169)	8.46(215)	66.5(30.2)
DC115-12	31	200	45	91	115	910	760	M8-TP08	12.91(328)	6.77(172)	8.66(220)	72.1(32.7)
DC140-12	DIN	260	62	115	140	950	795	M8-TP08	13.54(344)	6.77(172)	11.14(283)	95.0(43.1)
DC145-12	NA	279	86	122	145	975	820	M8	13.43(341)	6.81(173)	11.30(287)	97.7(44.3)
DC150-12	GC12	295	80	123	150	1050	900	M8-TP08	12.87(327)	7.71(182)	10.75(273)	93.9(42.6)
DC160-12	NA	300	82	130	160	1070	910	M8	19.06(484)	6.73(171)	9.49(241)	100.1(45.5)
DC210-12	4D	400	105	172	210	1425	1180	LT	20.87(530)	8.23(209)	8.58(218)	133.4(60.5)
DC215-12	921/J185	420	110	172	215	1200	100	DT	15.00(381)	7.00(178)	14.61(371)	132.3(60)
DC260-12	80	578	229	214	260	1830	1525	LT	20.51(521)	10.59(269)	8.82(224)	172.4(78.2)